

DIGITAL STILL CAMERAS

AVAILABILITY

MODEL	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC
DMC-TZ10			•	•	•	•	•	•	•	•	•	•
DMC-TZ8			•	•	•	•	•	•	•	•	•	•
DMC-FZ38EB-K	•	•	•	•	•	•	•	•	•	•	•	•
DMC-LX3EB-K	•	•	•	•	•	•	•	•	•	•	•	•
DMC-ZX3			•	•	•	•	•	•	•	•	•	•
DMC-FT2			•	•	•	•	•	•	•	•	•	•
DMC-FS33			•	•	•	•	•	•	•	•	•	•
DMC-FS30			•	•	•	•	•	•	•	•	•	•
DMC-FP3			•	•	•	•	•	•	•	•	•	•
DMC-FP1		•	•	•	•	•	•	•	•	•	•	•
DMC-FS11		•	•	•	•	•	•	•	•	•	•	•
DMC-FS10		•	•	•	•	•	•	•	•	•	•	•

TRAVEL ZOOM

DMC-TZ10

REPLACES: DMC-TZ7

INTRODUCTION: MARCH 2010



- 12MP
- 25mm Ultra Wide Angle
- 12x Optical Zoom
- GPS
- HD Movie (AVCHD Lite)
- Intelligent Auto
- 3" LCD
- Manual Mode (PASM)
- Leica Lens
- Lithium ION



TRAVEL ZOOM

DMC-TZ8

REPLACES: DMC-TZ6

INTRODUCTION: MARCH 2010



- 12MP
- 25mm Ultra Wide Angle
- 12x Optical Zoom
- HD Movie (M.JPEG)
- Intelligent Auto
- 2.7" LCD
- Manual Mode (PASM)
- Leica Lens
- Lithium ION



SUPER ZOOM

DMC-FZ38EB-K

REPLACES: DMC-FZ28
CURRENT MODEL



- 18x Optical Zoom
- iA
- 27mm Wide Angle
- 12MP
- 2.7" LCD
- Leica Lens
- HD Movie (AVCHD Lite)
- Lithium ION
- Manual Mode (PASM)



CREATIVE

DMC-LX3EB-K

REPLACES: DMC-LX2
CURRENT MODEL



- 24mm Wide Angle
- iA
- 2.4x Optical Zoom
- 10MP
- Manual Mode (PASM)
- HD Movie (M.JPEG)
- 2-2.8 Leica DC Vario-Summiron Lens
- Lithium ION



STYLISH COMPACT

DMC-ZX3

REPLACES: DMC-ZX1
INTRODUCTION: MARCH 2010



- 14MP
- 25mm Ultra Wide Angle
- 8x Optical Zoom
- HD Movie (AVCHD Lite)
- Compact Body
- Intelligent Auto
- 2.7" LCD
- Leica Lens
- Lithium ION



TOUGH

DMC-FT2

REPLACES: DMC-FT1

INTRODUCTION: MARCH 2010



- 14MP
- 10 Metres Waterproof
- 2 Metres Shockproof
- -10°C Freeze-Proof
- HD Movie (AVCHD Lite)
- 28mm Wide Angle
- 4.6x Optical Zoom
- Intelligent Auto
- 2.7" LCD
- Leica Lens
- Lithium ION



STYLISH COMPACT

DMC-FS33

REPLACES: DMC-FS25

INTRODUCTION: MARCH 2010



- 14MP
- 8x Optical Zoom
- 28mm Wide Angle
- 3" Touchscreen LCD
- Intelligent Auto
- HD Movie (M.JPEG)
- Lithium ION



STYLISH COMPACT

DMC-FS30

REPLACES: DMC-FS15

INTRODUCTION: MARCH 2010



- 14MP
- 8x Optical Zoom
- 28mm Wide Angle
- 2.7" LCD
- Intelligent Auto
- HD Movie (M.JPEG)
- Lithium ION



SLIM AND STYLISH

DMC-FP3

NEW MODEL
INTRODUCTION: MARCH 2010



- 14MP
- Slim Design
- 3" Touchscreen LCD
- 4x Optical Zoom
- Intelligent Auto
- HD Movie (M.JPEG)
- Lithium ION

SLIM AND STYLISH

DMC-FP1

NEW MODEL
INTRODUCTION: FEBRUARY 2010



- 12MP
- Slim Design
- 2.7" LCD
- 4x Optical Zoom
- Intelligent Auto
- HD Movie (M.JPEG)
- Lithium ION

STYLISH COMPACT

DMC-FS11

REPLACES: DMC-FS7
INTRODUCTION: FEBRUARY 2010



- 14MP
- 5x Optical Zoom
- 28mm Wide Angle
- 2.7" LCD
- Intelligent Auto
- HD Movie (M.JPEG)
- Lithium ION

STYLISH COMPACT

DMC-FS10

REPLACES: DMC-FS62
INTRODUCTION: FEBRUARY 2010



- 12MP
- 5x Optical Zoom
- 28mm Wide Angle
- 2.7" LCD
- Intelligent Auto
- HD Movie (M.JPEG)
- Lithium ION

SMALL AND LIGHTWEIGHT WITH AVCHD LITE

DMC-GF1

CURRENT MODEL

Available in Black, Red and Silver

Available Kits:

- Body Only
- 14-45mm Lens Kit
- 20mm Pancake Lens Kit



- 4/3" 12.1 Megapixel LIVE MOS Sensor
- Compact Aluminium Body
- Interchangeable Lens System
- 3.0" High Resolution LCD (460k dots)
- Ultra Fast Auto Focus System
- Movie Mode – AVCHD Lite
- Built-in Pop-Up Flash
- Intelligent Auto Mode

New-Generation System Cameras

LUMIX G™
MICRO SYSTEM

WV
MICRO
FOURTHIRDS

iA
PHOTO & MOVIE



AVCHD Lite

HDMI™
HIGH-DEFINITION MULTIMEDIA INTERFACE

SD
HC

INTERCHANGEABLE LENS CAMERA WITH FULL HD MOVIE RECORDING

DMC-GH1

CURRENT MODEL

Available in Black and Red

Available Kits:

- Body Only
- 14-140mm Lens Kit



- Full HD Movie 1920x1080, 25p
- 4/3 type 12.1 Megapixel Live Mos Sensor
- Full-Time Live View Function
- Live View Finder (100% Field of View)
- 3.0" Free Angle LCD (460k dots)
- Intelligent Auto Mode Technology with Face Recognition
- Micro Four Thirds Mount

New-Generation System Cameras

LUMIX G™
MICRO SYSTEM

WV
MICRO
FOURTHIRDS

iA
PHOTO & MOVIE



FULL HD
1920x1080

AVCHD

HDMI™
HIGH-DEFINITION MULTIMEDIA INTERFACE

SD
HC

12.1 MEGAPIXEL ULTRA COMPACT DIGITAL SYSTEM CAMERA

DMC-G1

CURRENT MODEL

Available in Black, Red and Blue

Available Kits:

- 14-45mm Lens Kit



- 4/3" 12.1 Megapixel LIVE MOS Sensor
- Full-Time Live View Function
- Interchangeable Lens System
- 3.0" Free-Angle LCD (460k dots)
- Face Detection, AF and AE
- Micro Four Thirds Mount
- Additional Features
Supersonic Wave Filter for dust reduction, Shutter speed: bulb, 60-1/4000 sec, Venus Engine HD LSI image processor, ISO setting up to 3200 and Intelligent ISO control, 3fps burst rate, continuous shooting up to memory card capacity, Hot shoe, TTL auto for Panasonic flashes DMW-FL220, DMW-FL360 and DMW-FL500, JPEG and RAW format recording, SD memory card slot, USB 2.0 Hi-Speed, Incl. Lumix G VARIO Lens 14-45mm (28-90mm equiv.)/F3.5-5.6 with Mega O.I.S.

New-Generation System Cameras

LUMIX G™
MICRO SYSTEM

WV
MICRO
FOURTHIRDS

iA
PHOTO & MOVIE



HDMI™
HIGH-DEFINITION MULTIMEDIA INTERFACE

SD
HC



New G Series Lenses

Coming Soon in 2010, including:

8mm F3.5 Fisheye Lens

100-300mm F4.0-5.6 Telephoto Lens

14mm F2.5 Pancake Lens

New-Generation System Cameras

LUMIX G™
MICRO SYSTEM

LUMIX G VARIO 14-45mm ULTRA COMPACT LENS H-FS014045

- 14-45mm Focal Length
35mm equiv.: 28-90mm
- O.I.S. Optical Image Stabiliser
- Micro Four Thirds Standard Metal Mount
- Filter Size: 52mm
- Aperture: F3.5-5.6
- Minimum Shooting Distance: 0.3m
- Weight: 195g



LUMIX G VARIO 45-200mm TELEPHOTO ZOOM LENS H-FS045200

- 45-200mm Focal length
35mm equiv.: 90-400mm
- O.I.S. Optical Image Stabiliser
- Micro Four Thirds Standard Metal Mount
- Filter Size: 52mm
- Aperture: F4.0-5.6
- Minimum Shooting Distance: 1.0m
- Weight: 380g



LUMIX G VARIO HD LENS 10x OPTICAL ZOOM H-VS014140

- 14-140mm Focal Length
(35mm equiv. 28-280mm)
- O.I.S. Optical Image Stabiliser
- Micro Four Thirds Standard Metal Mount
- Filter Size: 62mm
- Aperture: F4.0-5.8
- Minimum Shooting Distance: 0.5m
- HD Movie Recording
- Silent Operation
- Weight: 470g



LUMIX G VARIO LENS ULTRA WIDE ANGLE H-F007014

- 7-14mm Focal Length
(35mm equiv. 14-28mm)
- Micro Four Thirds Standard Metal Mount
- Aperture: F4.0
- Minimum Shooting Distance: 0.25m
- Lens Construction 16 elements
- Compact Size:
83.1mm (length)
- Weight: 300g



LUMIX G VARIO 20mm PANCAKE LENS H-H020

- 20mm Focal Length (35mm equiv. 40mm)
- Wide Depth of Field
- Micro Four Thirds Standard Metal Mount
- Filter Size: 46mm
- Aperture: F1.7
- Minimum Shooting Distance: 0.2m
- Weight: 100g



LUMIX DG MACRO ELMARIT 45mm LENS H-ES045

- 45mm Focal Length (35mm equiv. 90mm)
- O.I.S. Optical Image Stabiliser
- Micro Four Thirds Standard Metal Mount
- Filter Size: 46mm
- Aperture: F2.8
- Minimum Shooting Distance: 0.15m
- Weight: 225g

LEICA
DG LENS



With the mount adaptor DMW-MA1, all Four Thirds lenses can be used with the GH1, G1 and GF1.